

TITAN 05

**BALER BELT FASTENERS WITH PRE-MOUNTED STAPLES
FOR BELTS WITH A THICKNESS FROM 5 TO 7 mm (3/16" TO 9/32")
AND A MAXIMUM WORKING TENSION OF 65 kN/m (360 PIW)**

FASTENERS:

Stainless steel

STAPLES:

Stainless steel, pre-mounted in line.

CONNECTING PIN:

Grooved Stainless steel, Ø 3.2 mm (1/8")
Flexible Stainless steel nylon coated 3 mm (1/8")



PACKAGING:

Box of 12 strips of 10 elements 150 mm (6")
+Six 160 mm (6.3/8") rods.
For use on 168 mm (6.39/64") to 178 mm (7") wide baler belts.

Reference with flexible pin	Strip Length	Belt Thickness	Minimum Pulley Ø	Price per box
109101	150 mm (6")	5 to 7 mm (3/16" to 9/32")	80 mm (3 3/16")	£92.26

APPLICATIONS MACHINE AND TOOLS

T183 vice Tool: Mounted on a vice, it allows the splicing of a 180 mm (7") wide belt (10 fasteners) in one setting and is open-ended for continuous lacing for wider belts.

Reference	Description	Price
109201	T183 : L :175 mm (7")	£243.65

